

MATCH
MACHINERY

MATCH EXCAVATOR



TIANJIN MATCH MACHINERY CO.,LTD

Wechat:+8617802220729

WhatsApp:+8617802220729

Email:kenny@tj-echain.com

Website:www.match-machinery.com

Address:Room 605,#1 Building, Golden Valley Mansion, 1 Binjiang Avenue, Heping District, Tianjin

MC65

Super strong configuration, excellent performance, import configuration, Domestic famous brand engine, strong power, to meet the efficient operation requirements.

Accurate matching design and advanced energy saving control make the machine less fuel,consumption, Low emissionSuper strong configuration, excellent performance, import configuration.

Domestic famous brand engine, strong power, to meet the efficient operation requirementsAccurate matching design and advanced energy saving control make the machine less fuel consumption, Low emission.

The use of new cooling fans and large mufflers makes the noise of the machine lower.

The advanced turbocharging technology is used to enhance the adaptability of the high altitude machine.

The unique funnel type fan cover greatly improves the engine's air intake and the ability of the system to heat the heat, so as to ensure the continuous and efficient operation of the machine.

超强配置，性能卓越，进口配置，国产名牌发动机，动力强劲，满足高效作业需求。

精准的匹配设计，先进的节能控制，使整机油耗更低消耗低，低排放超强配置，性能卓越，进口配置。

国产名牌发动机，动力强劲，满足高效作业要求精准的匹配设计，先进的节能控制使机器燃料消耗更少，低排放。

采用新型冷却风扇和大型消声器，使机器噪音更低。

采用先进的涡轮增压技术，增强了机器的高海拔适应性。

独特的漏斗型风扇罩大大提高了发动机的进气量和系统散热的能力，从而保证机器连续、高效运转。



技术参数

Machine Detailed Parameters

Performance Parameter性能参数	
Bucket Capacity铲斗容量 (M³)	0.21
Swing Speed挥杆速度 (Rmp)	0-11
Gradeability爬坡度(°)	35
Bucket Max.Digging Force铲斗最大挖掘力(KN)	48
Arm Max.Digging Force斗杆最大挖掘力(KN)	35
Engine Model发动机型号	KUBO*TA V2607
Power/Rotation Speed功率/转速(KW/Rmp)	42.4/2000
Tyre Model轮胎型号	-
System Pressure系统压力(MPa)	28
Working Range工作范围	
Max.Digging Height最大挖掘高度(mm)	5499
Max. Dumping Height最大卸载高度(mm)	3845
Max.Digging Depth最大挖掘深度(mm)	3808
Max.Vertical Digging Depth最大垂直挖掘深度(mm)	2983
Max.Digging Radius最大挖掘半径(mm)	6128
Min.Swing Radius最小回转半径(mm)	2607
Dozer Blade Max.Lifting Height推土铲最大提升高度(mm)	376
Dozer Blade Max.Cutting Depth推土铲最大切削深度(mm)	474
Dimensions尺寸	
Length*Width*Height长*宽*高(mm)	5940*1880*2570
Cabin Height客舱高度(mm)	2600
Sproket To Idler链轮至惰轮距离(mm)	1990
Axle Distancer轴距(mm)	1480
Min.Ground Clearance最小离地间隙(mm)	353
Tail Swing Radius尾部回转半径(mm)	1689

MC75

- 1,Fitted famous brand main pump and valves and driving motor and slewing motor.
- 2,Adopted hydraulic pilot servo operation system and hydraulic oil radiator, ensure the machine have high working efficiency .
- 3,The professional structural parts and working mechanism , ensure the machine has reliability and durability .
- 4,The breaking pipeline equipped improve the working performance .
- 5,Installed luxury full seal cabin with A/C and LCD display etc.
- 6,The humanized design , ensure the machine can comfortable operation and convenient maintenance.

- 1、采用名牌主泵、阀、驱动电机、回转马达。
- 2、采用液压先导伺服操作系统及液压油散热器，确保机器具有较高的工作效率。
- 3、专业的结构件和工作机构，保证机器的可靠性和耐用性。
- 4、配备破碎管路，提高工作性能。
- 5、安装豪华全密封驾驶室，配有空调、液晶显示屏等。
- 6、人性化的设计，确保机器操作舒适、维护方便。



技术参数

Machine Detailed Parameters

ENGINE发动机	
Emission Standard排放标准	Tier 3/ Stage III
Make /Model品牌/型号	IMPORTED(V2607)
Power /Rotation speed功率/转速	42.4kw(58HP)@2000rpm
Number of cylinder气缸数	4
TRACK SYSTEM操作系统	
Maximum Travel speed最大行驶速度	2.5/4.5km/h
Width of track shoe履带板宽度	450mm
Number of track shoe per side每侧履带板数量	39pcs
Number of upper roller per side每侧上辊数量	1
Number of bottom roller per side每侧下辊数量	5
PERFORMANCE PARAMETER性能参数	
Standard Bucket capacity标准铲斗容量	0.28m³
Swing speed挥杆速度	11rpm
Maximum Grade ability最大爬坡能力	35°
Maximum Bucket digging force铲斗最大挖掘力	56KN
Maximum Arm digging force斗杆最大挖掘力	38KN
Hydraulic system pressure液压系统压力	27Mpa
Machine weight机器重量	7500kg
Fuel tank燃油箱	120L
Hydraulic oil tank液压油箱	100L
MACHINE SIZE机器尺寸	
Overall dimension (L*W*H)外形尺寸（长*宽*高）	6054mm*2216mm*2672mm
Height of cabin机舱高度	2672mm
Track length on ground(Axle base)履带接地长度（轴距）	2209mm
Track gauge轨距	1745mm
Minimum Ground clearance最小离地间隙	375mm
Swing radius at tail尾部摆动半径	1730mm
WORKING RANGE工作范围	
Maximum Digging height最大挖掘高度	7023mm
Maximum Dumping height最大卸载高度	5195mm
Maximum Digging depth最大挖掘深度	3898mm
Maximum Vertical digging depth最大垂直挖掘深度	2968mm
Maximum Digging radius最大挖掘半径	6182mm
Minimum swing radius最小回转半径	1740mm
Maximum Lifting height of blade铲刀最大提升高度	382mm
Maximum Cutting depth of blade刀片最大切割深度	332mm

MC90

- 1、The crawler excavator is an economic type excavator, which matched imported engine with strong power and low noise and low consumption and environment protection.
- 2、Fitted imported brand main pump and valves .
- 3、Adopted imported driving motor and swing motor.
- 4、Adopted hydraulic pilot servo operation system and hydraulic oil radiator, ensure the machine have high working efficiency .
- 5、The professional structural parts and working mechanism , ensure the machine has reliability and durability .
- 6、The breaking pipeline equipped improve the working performance .
- 7、Installed luxury full seal cabin with A/C and LCD display etc.
- 8、The humanized design , ensure the machine can comfortable operation and convenient maintenance.

- 1、该履带挖掘机为经济型挖掘机，配套进口发动机，动力强劲，噪音低，消耗低，环保。
- 2、采用进口品牌主泵及阀门。
- 3、采用进口驱动电机、摆动电机。
- 4、采用液压先导伺服操作系统及液压油散热器，确保机器具有较高的工作效率。
- 5、专业的结构件和工作机构，保证机器的可靠性和耐用性。
- 6、配备破碎管路，提高工作性能。
- 7、安装豪华全密封驾驶室，配有空调、液晶显示屏等。
- 8、人性化的设计，确保机器操作舒适、维护方便。



技术参数

Machine Detailed Parameters

Performance Parameter性能参数	
Bucket Capacity铲斗容量(m³)	0.4
Swing Speed回转速度 (r/min)	0-12
Gradeability爬坡能力(°)	35
Bucket Max.Digging Force铲斗最大挖掘力(KN)	58
Arm Max.Digging Force斗杆最大挖掘力(KN)	40
Engine Model发动机型号	QSF2.8
Power/Rotation Speed 功率/转速 (KW/Rmp)	53/2200
Tyre Model轮胎型号	-
System Pressure系统压力(MPa)	27.5
Working Range工作范围	
Max.Digging Height最大挖掘高度(mm)	7050
Max. Dumping Height最大卸载高度(mm)	5188
Max.Digging Depth最大挖掘深度(mm)	4015
Max.Vertical Digging Depth最大垂直挖掘深度(mm)	3550
Max.Digging Radius最大挖掘半径(mm)	6540
Min.Swing Radius最小回转半径(mm)	2140
Dozer Blade Max.Lifting Height推土铲最大提升高度(mm)	370
Dozer Blade Max.Cutting Depth推土铲最大切削深度(mm)	344
Dimensions尺寸	
Length*Width*Height长*宽*高(mm)	6410*2278*2630
Cabin Height驾驶室高度 (mm)	2630
Sproket To Idler驱动轮至导向轮的中心距(mm)	2209
Axle Distancer(mm)轴距(mm)	1750
Min.Ground Clearance(mm)最小离地间隙 (mm)	375
Tail Swing Radius(mm)尾部回转半径(mm)	1813

MC150

Advanced Hydraulic System:
Equipped with closed-circuit hydraulic system design for improved energy efficiency,
Provides smooth operation and precise control of all movements,
Delivers maximum bucket digging force for enhanced productivity.

Powerful Performance:
73kW engine ensures strong power output for demanding tasks
Two-speed hydraulic motor for walking drive allows optimal speed selection,
30° gradeability enables operation on various terrains.

Durable Crawler System:
Heavy-duty crawler undercarriage provides excellent stability,
Floating track design reduces ground pressure (below 15kPa) for soft terrain operation,
Enhanced traction for challenging working conditions.

先进的液压系统:
配备闭式液压系统提高能源效率的设计，
提供运行平稳和精确控制所有运动，
交付铲斗最大挖掘力提高生产力。

强大的性能:
73千瓦发动机确保高要求任务的强大动力输出，
双速液压马达步行驱动允许选择最佳速度，
30°爬坡能力可在各种地形上作业。

耐用的履带系统:
重型履带式底盘提供出色的稳定性，
浮动轨道设计降低地面压力（低于 15kPa），适合软地形作业，
增强牵引力适用于具有挑战性的工作条件。



技术参数 Machine Detailed Parameters

Specifications规格	
Bucket Capacity铲斗容量	0.6m³
Swing Speed回转速度	0-12 r/min
Grade ability爬坡能力	30°
Max.Bucket Digging Force铲斗最大挖掘力	90kN
Max.Arm Digging Force斗杆最大挖掘力	55kN
Engine Model发动机型号	ISUZU 4JJ1
Power/revolution speed功率/转速	73Kw/2000rpm
Tire Model轮胎型号	
System Pressure系统压力	32Kpa
Machine size机器尺寸	
Dimension Length*Width*Height尺寸长*宽*高	7635x2500x2750mm
Cabin Height驾驶室高度	2750mm
Axle Base轴距	2950mm
Wheel(track) Distance轮距（轮距）	2000mm
Minimum ground clearance最小离地间隙	400mm
Tail Swing Radius尾部回转半径	2340mm
Working range工作范围	
Max.Digging Height最大挖掘高度	8540mm
Max.Dumping Height最大卸载高度	6125mm
Max.Digging Depth最大挖掘深度	5095mm
Max.Vertical Digging Depth最大垂直挖掘深度	4650mm
Max.Digging Radius最大挖掘半径	8000mm
Min.Swing Radius最小回转半径	2445mm

MC180

MC180 crawler excavator is a china famous brand MATCH, which researched and developed with world latest technical standard. it is a new kind of product characterized by high efficiency , safety, convenience, beauty.

Steel track, with dozer blade.

Hydraulic pilot servo handle controlling system ,easy to operation .

Adopted the YUCHAI or CUMMINS brand engine with strong power.

Imported international brand hydraulic system , ensure the machine has high working efficiency.

The professional structure parts and working mechanism , ensure the machine has reliability and durability.

The breaking pipeline improve the working performance.

MC180履带式挖掘机是中国著名品牌迈驰公司采用世界最新技术标准研发的一款高效、安全、便捷、美观的新型产品。
钢制履带，带推土铲。

液压先导伺服手柄控制系统，操作方便。

采用玉柴或康明斯品牌发动机，动力强劲。

进口国际品牌液压系统，确保机器具有较高的工作效率。

专业的结构件和工作机构，确保机器的可靠性和耐用性。

破碎管路提高了工作性能。



技术参数

Machine Detailed Parameters

Description描述	Unit-Metric
Overall length总长度	8540mm
Overall width总宽度	2720mm
Overall height总高度	2920mm
Cabin height驾驶室高度	2920mm
Track length on ground履带地面长度	3200mm
Track gauge轨距	2120mm
Min.ground clearance最小离地间隙	480mm
Swing radius at tail尾部回转半径	2430mm
Max.digging height最大挖掘高度	9430mm
Max.dumping height最大卸载高度	6960mm
Max.digging depth最大挖掘深度	5975mm
Max.vertical digging depth最大垂直挖掘深度	5630mm
Max.digging radius最大挖掘半径	8985mm
Min.swing radius最小回转半径	2725mm
Bucket capacity铲斗容量	0.8m³
swing speed挥杆速度	0~12rpm
Max.grade ability最大爬坡能力	30°
Max.digging force of grab抓斗最大挖掘力	98KN
Max.digging force of arm斗杆最大挖掘力	68KN
Engine model/power发动机型号/功率	YUCHAI YC4A140, 103kw/2200r/min
	CUMMINS QSF3.8, 93kw/2200rpm
Track width履带板宽度	600mm
System pressure系统压力	32Mpa



MC220

Adoption of new intelligent electronic control system, effectively realizing man-machine dialogue. Accurate micro-operation, flexible and coordinated compound operation, and perfect movement. Equipped with a buffer valve to reduce the impact of the operation. The arm priority function greatly improves the efficiency and stability of the whole machine. Adopting frame structure, equipped with unique shaped pipe column, it can meet the requirement of high strength and rigidity cab for ROPS/FOPS hydraulic excavators, improve the strength of cab, and effectively protect the driver's personal safety.

采用全新智能电控系统，有效实现人机对话。
精准的微动操作，灵活协调的复合操作，动作完美。
配备缓冲阀，降低操作冲击。
动臂优先功能，大幅提升整机效率和稳定性。
采用框架结构，配备独特造型的管柱，满足ROPS/FOPS液压挖掘机对驾驶室高强度、高刚度的要求，提升驾驶室强度，有效保护驾驶员人身安全。



技术参数 Machine Detailed Parameters

Engine发动机			Travel System行走系统			
Mode型号		Cummins6BTAA5.9	Travel motors行走马达		Variable axial piston motor可变轴向柱塞马达	
Type类型		6 cylinders; turbo charged; direct injection,water cooled6缸；涡轮增压；直喷，水冷	Travel brakes行驶制动器		Hydraulic disc brake液压盘式制动器	
No. of cylinder气缸数		6	Parking brakes驻车制动器		Oil release油释放	
Bore and stroke缸径和冲程		102X120(mm)	Travel shoes履带板数量		2X46	
Displacement排量		5.9L	No.of Travel speed行驶速度		3.1/5.1 (km/h)	
Power output额定功率		133kw/2000rpm	Drawbar pulling force牵引力		214kN	
Max. torque最大扭矩		708N.m/1500rpm	Grade ability爬坡能力		70%(35°)	
			Ground clearance离地间隙		470mm	
Hydraulic System 液压系统			Cab & Controls驾驶室和控制装置			
Pump 泵 imported进口			Cab驾驶室	New ergonomic cab, which strengthens the structure of the entire stamping, with the features: strong impact resistance, vibration damping pads, absorbing vibration, work comfortably.全新人机工程驾驶室，强化整体冲压结构，具有：抗冲击能力强，减震垫，吸收震动，工作舒适		
Type类型	Variable double-piston pump可变量双柱泵					
Max. discharge flow最大排放流量		2x224(L/min)				
Max. discharge pressure最大排放压力			Control控制	Two hand levers and two foot pedals for travel; Two hand levers for excavating and swing两个手柄和两个脚踏板旅行；两个用于挖掘和摆动的手柄 Electric rotary-type throttle电动旋转式油门		
Boom,arm and bucket动臂、斗杆和铲斗		34.3MPa				
Travel circuit行走回路压力		34.3MPa				
Swing circuit回转回路压力		25.5 MPa				
Control circuit控制回路压力		3.9MPa		Boom, Arm & Bucket动臂、斗杆&铲斗		
Type of Pilot control pump先导控制泵的类型		Gear pump齿轮泵		Boom cylinder动臂油缸		Φ120XΦ85X1335 (mm)
Main control valves主控制阀		Negative flow control system负流量控制系统		Arm cylinder斗杆油缸		Φ135XΦ95X1490 (mm)
Oil cooler油冷却器		Air cooler空气冷却器		Bucket cylinder铲斗油缸		Φ115XΦ80X1120 (mm)
Swing System回转系统			Refilling Capacities & lubrications加注容量与润滑规范			
Swing motor type回转马达类型		Swashplate-piston motor斜盘式柱塞马达		Fuel tank燃油箱		330L
Brake制动		Oil release液压制动		Cooling system冷却系统		28L
Parking brake驻车制动器		Hydraulic disc液压盘		Engine oil机油		22L
Swing speed回转速度		10.8r/min		Swing reduction gear回转减速机		4L
Tail swing radius尾部回转半径		2925mm		Hydraulic oil tank液压油箱		250L/400L
Bucket铲斗			Backhoe bucket反铲铲斗			
Use使用			Bucket capacity铲斗容量			1.06m³
			No. of bucket teeth斗齿数量			5
			Bucket width铲斗宽度			1254mm
Working ranges工作范围						
Arm length臂长			2.925m			
A	Max. digging reach最大挖掘范围		9.86m			
B	Max. digging reach at ground level地面最大挖掘范围		9.675m			
C	Max. digging depth最大挖掘深度		6.49m			
D	Max. digging heigh最大挖掘高度		10.95m			
E	Max. dumping height最大卸载高度		7.19m			
F	Max. vertical wall digging depth最大垂直墙体挖掘深度		5.915m			
G	Min. swing radius of work equipment最小回转半径		2.97m			
I	Bucket capacity铲斗容量		1.06m³			
Digging Force 挖掘力 ((ISO6015)						
Range范围			Parameters参数			
A	Arm length臂长		2925mm			
B	Bucket digging force铲斗挖掘力		146KN			
C	Arm digging force斗杆挖掘力		107KN			
Overall Dimensions 外形尺寸			Unit 单位: mm			
Arm length臂长			2925mm			
A	Overall length总长度		G	Tail swing radius尾部回转半径	2925mm	
B	Overall height (to top of boom)总高度（至动臂顶部）		H	Tumbler distance轮距	3360mm	
C	Overall width总宽度		I	Overall length of crawler履带总长度	4140mm	
D	Overall height (to top of cab)总高度（至驾驶室顶部）		J	Track gauge轨距	2200mm	
E	Ground clearance of rear end配重离地间隙		K	Shoe width履带板宽	600mm	
F	Min.Ground clearance最小离地间隙		L	Overall width of upperstructure转台宽度	2725mm	
Operating Weight and Ground Pressure工作重量和地面压力						
Shoe width履带板宽度			600mm			
Overall width总宽度			2800mm			
Ground pressure接地比压			47.5KPa			
Operating weight工作重量			21200Kg			

MC230

Enhanced Structural Design:
Increased cross-section depth of boom and arm for improved durability,
Cast steel construction in critical stress areas for maximum strength.

Powerful & Efficient Engine:
Engine delivers 133kW power output at 2000 rpm,
Low fuel consumption design reduces operating costs,
High torque at low RPM for better performance in demanding applications.

Advanced Hydraulic System:
Closed-circuit hydraulic system for improved energy efficiency,
Precise control of all movements with smooth operation,
Optimized hydraulic circuits for faster cycle times and higher productivity.

增强的结构设计:
增加横截面深度动臂和斗杆的耐用性得到提高,
铸钢结构在关键应力区域实现最大强度。

强劲高效的引擎:
发动机交付133kW 功率输出2000 rpm ,
低油耗设计降低了运营成本,
低转速高扭矩在要求严苛的应用中实现更佳性能。

先进的液压系统:
闭式液压系统提高能源效率,
精确控制运行顺畅,
优化的液压回路缩短循环时间, 提高生产率。



技术参数

Machine Detailed Parameters

Specifications规格	
Bucket Capacity铲斗容量	1.1m ³
Swing Speed回转速度	11-13r/min
Grade ability爬坡能力	30°
Max.Bucket Digging Force铲斗最大挖掘力	140kN
Max.Arm Digging Force斗杆最大挖掘力	99kN
Engine Model发动机型号	6BTAA5.9-C178
Power/revolution speed功率/转速	133Kw/2000rpm
Tire Model轮胎型号	-
System Pressure系统压力	34Mpa
Machine size机器尺寸	
Dimension Length*Width*Height尺寸长*宽*高	9590x2980x3185mm
Cabin Height驾驶室高度	3060mm
Axle Base轴距	3655mm
Wheel(track) Distance轮距 (轮距)	2380mm
Minimum ground clearance最小离地间隙	470mm
Tail Swing Radius尾部回转半径	2880mm
Working range工作范围	
Max.Digging Height最大挖掘高度	9410mm
Max.Dumping Height最大卸载高度	6730mm
Max.Digging Depth最大挖掘深度	6480mm
Max.Vertical Digging Depth最大垂直挖掘深度	5925mm
Max.Digging Radius最大挖掘半径	9850mm
Min.Swing Radius最小回转半径	3555mm

MC380

Equipped with the internationally recognized original imported Isuzu 6HK1X six-cylinder engine, National III emission standard, excellent performance, energy saving and environmental protection, convenient maintenance.

The original imported Germany Linde hydraulic system (one of the world's three top hydraulic systems), to ensure the high stability and reliability of the product.

Linde Load Sensing Pumps, Load Sensing Control, Automatic Power Matching, Flow on Demand, Reduced Power Losses.

Linde rotary motors, good low-speed stability, high starting torque, high reliability, long service life; fast dynamic response, streamlined power transmission system.

Load-sensitive synchronized control valve, pressure compensation technology, even in complex mines, can be operated freely, improving coordination and operational efficiency.

Adopting frame structure, equipped with unique shaped pipe column, it can meet the requirement of high strength and rigidity cab for ROPS/FOPS hydraulic excavators, improve the strength of cab, and effectively protect the driver's personal safety.

搭载国际认可的原装进口五十铃6HK1X六缸发动机，符合国三排放标准，性能卓越，节能环保，维护便捷。

原装进口德国林德液压系统（世界三大顶级液压系统之一），确保产品高稳定性和可靠性。

林德负载敏感泵，负载敏感控制，自动功率匹配，按需流量，降低功率损耗。

林德旋转马达，低速稳定性好，启动扭矩大，可靠性高，使用寿命长；动态响应快，精简的动力传动系统。

负载敏感同步控制阀，压力补偿技术，即使在复杂的矿山环境下也能操作自如，提高协调性和作业效率。

采用框架结构，配备独特造型的管柱，满足ROPS/FOPS液压挖掘机对驾驶室高强度和刚度的要求，提高驾驶室强度，有效保护驾驶员的人身安全。



技术参数

Machine Detailed Parameters

Operating Weight and Ground Pressure工作重量和接地比压	
Operating weight工作重量	37000Kg
Ground pressure接地比压	62KPa
Engine发动机	
Mode型号	Isuzu 6HK1X
Type类型	6 cylinder inline; turbocharged;intercooling
No. of cylinder气缸数	6
Bore and stroke缸径和冲程	6X115X125(mm)
Displacement排量	7.79L
Power output功率输出	212kw/2000rpm
Hydraulic System液压系统	
Type类型	2Variable pluger pump + 1 gear pump
Travel circuit行走回路压力	36MPa
Swing circuit回转回路压力	25.5 MPa
Bucket铲斗	
Bucket capacity铲斗容量	1.8m3
Bucket width铲斗宽度	1571mm
Travel System行走系统	
Travel motors行走马达	Variable axial piston motor
Travel brakes行驶制动器	Pressure Release Mechanical Braking
Parking brakes驻车制动器	Oil release
Gradeability爬坡能力	70%(35°)
Ground clearance离地间隙	565mm
Working Ranges工作范围	
Max. digging reach at ground level地面最大挖掘范围	10460mm
Max. digging depth最大挖掘深度	6759mm
Max. digging heigh最大挖掘高度	10125mm
Max. dumping height最大卸载高度	6969mm
Max. vertical wall digging depth最大垂直墙体挖掘深度	5572mm
Overall length总长度	11161mm
Overall height (to top of boom)总高度（至动臂顶部）	3347mm
Overall width总宽度	3200mm
Shoe width履带宽度	600mm
Overall height (to top of cab)总高度（至驾驶室顶部）	3293mm
Ground clearance of rear end配重离地间隙	1312mm
Min.Ground clearance最小离地间隙	565mm

MC380J

Large Excavator Mining Excavator MATCH MC380J 37Ton 38Ton 40Ton 38Ton 40Ton Crawler Excavator.
MATCH Excavator MC380J excavator is a crawler-type machine designed for heavy-duty operations.
The MATCH MC380J large crawler excavator combines exceptional performance, high reliability, and user-friendly design.
It excels in multiple core configurations and technologies, delivering exceptional operating efficiency and durability.
Key features include:
Equipped with a high-power engine from a renowned brand, it delivers ample power to meet the demands of high-intensity operations.
The system's precise matching and optimized energy-saving controls significantly reduce fuel consumption.

大型挖掘机 矿用挖掘机 MATCH MC380J 37吨 38吨 40吨 38吨 40吨 履带式挖掘机。
MATCH MC380J 挖掘机是一款专为重载作业而设计的履带式机器。
MATCH MC380J 大型履带式挖掘机集卓越性能、高可靠性和人性化设计于一身。
它采用多项核心配置和技术，拥有卓越的作业效率和耐用性。
主要特点包括：
搭载知名品牌大功率发动机，动力充沛，满足高强度作业需求。
系统的精准匹配和优化的节能控制，显著降低油耗。



技术参数

Machine Detailed Parameters

Specifications性能参数	
Bucket Capacity挖斗容量(m³)	1.7
Swing Speed回转速度(rmp)	0-11
Gradeability最大爬坡角度(°)	35
Max.Bucket Digging Force挖斗最大挖掘力(KN)	244
Max.Arm Digging Force斗杆最大挖掘力(KN)	200
Engine Model发动机型号	SL9
Power/revolution speed功率/转速(KW/rmp)	219/1900
Tire Model轮胎型号	—
System Pressure系统压力(MPa)	35
Machine size整机尺寸	
Dimension Length*Width*Height外形尺寸长x宽x高(mm)	11285x3190x3664
Cabin Height驾驶室高(mm)	3168
Axle Base轴距(mm)	4099
Wheel(track) Distance轮(轨)距(mm)	2590
Minimum ground clearance最小离地间隙(mm)	536
Tail Swing Radius尾部回转半径(mm)	3590
Working range作业范围	
Max.Digging Height最大挖掘高度(mm)	10511
Max.Dumping Height最大卸载高度(mm)	7572
Max.Digging Depth最大挖掘深度(mm)	7372
Max.Vertical Digging Depth最大垂直挖深(mm)	6731
Max.Digging Radius最大挖掘半径(mm)	11178
Min.Swing Radius最小回转半径(mm)	3865



MC470

MC470 series products improve efficiency by 12% and reduce fuel consumption by 8% compared to the original-8 products.
Cummins QSM11 engine, reliable, high efficiency, low fuel consumption.
Adopting electronic control for high-pressure fuel injection to optimize fuel injection and reduce fuel consumption.
Synchronized control reduces excess engine rotation under light operation, reducing fuel consumption and noise.

MC470系列产品较原有8款产品效率提高12%，油耗降低8%。
康明斯QSM11发动机，可靠、高效、低油耗。
采用电子控制高压燃油喷射，优化燃油喷射，降低油耗。
同步控制减少轻载工况下发动机过度旋转，降低油耗和噪音。



技术参数

Machine Detailed Parameters

Operating Weight and Ground Pressure工作重量和接地比压	
Operating weight工作重量	44900Kg
Ground pressure接地比压	80.2KPa
Engine发动机	
Mode模式	Cummins QSM11
Type类型	6 cylinder inline; turbocharged;intercooling
No. of cylinder气缸数	6
Bore and stroke缸径和冲程	6X125X150(mm)
Displacement排量	11L
Power output功率输出	250kw/2000rpm
Hydraulic System液压系统	
Type类型	2 Variable pluger pump + 1 gear pump
Travel circuit行走回路压力	34.3MPa
Swing circuit回转回路压力	28.4MPa
Swing speed回转速度	9.3r/min
Bucket铲斗	
Bucket capacity铲斗容量	2.0-2.2m³
Bucket width铲斗宽度	1350-1530mm
Travel System行走系统	
Travel motors行走马达	Variable axial piston motor
Travel shoes履带板数量	2X49
Travel speed行驶速度	5.3/3.2km/h
Travel brakes行驶制动器	Pressure Release Mechanical Braking
Grade ability爬坡能力	70%(35°)
Ground clearance离地间隙	557mm
Working Ranges工作范围	
Arm length斗杆长度	3381mm
Max. digging reach at ground level地面最大挖掘范围	11814mm
Max. digging depth最大挖掘深度	7800mm
Max. digging heigh最大挖掘高度	10924mm
Max. dumping height最大卸载高度	7615mm
Max. vertical wall digging depth最大垂直挖掘深度	7066mm
Overall length总长度	12090mm
Overall height (to top of boom)总高度（至动臂顶部）	3590mm
Overall width总宽度	3490mm
Shoe width履带宽度	600mm
Overall height (to top of cab)总高度（至驾驶室顶部）	3276mm
Ground clearance of rear end配重离地间隙	1312mm
Min.Ground clearance最小离地间隙	686mm

MC500

MC500 series products improve efficiency by 12% and reduce fuel consumption by 8% compared to the original-8 products.
Cummins QSM11 engine, reliable, high efficiency, low fuel consumption.
Adopting electronic control for high-pressure fuel injection to optimize fuel injection and reduce fuel consumption.
Synchronized control reduces excess engine rotation under light operation, reducing fuel consumption and noise.

MC500 系列产品与原 8 系列产品相比，效率提高了 12%，燃油消耗降低了 8%。
康明斯 QSM11 发动机，可靠、高效、低油耗。
采用高压燃油喷射电子控制技术，优化燃油喷射，降低油耗。
同步控制减少轻载运行时发动机的空转，降低油耗和噪音。



技术参数

Machine Detailed Parameters

Operating Weight and Ground Pressure工作重量和接地比压	
Operating weight工作重量	49600Kg
Ground pressure接地比压	81.9KPa
Engine发动机	
Mode模式	Cummins QSM11
Type类型	6 cylinder inline; turbocharged;intercooling
No. of cylinder气缸数	6
Bore and stroke缸径和冲程	6X125X150(mm)
Displacement排量	7.79L
Power output功率输出	280kw/2000rpm
Hydraulic System液压系统	
Type类型	2Variable pluger pump + 1 gear pump
Travel circuit行走回路压力	34.3MPa
Swing circuit回转回路压力	28.4MPa
Swing speed回转速度	9.3r/min
Bucket铲斗	
Bucket capacity铲斗容量	1.8m³
Bucket width铲斗宽度	1968mm
Travel System行走系统	
Travel motors行走马达	Variable axial piston motor
Travel shoes履带板数量	2X50
Travel speed行驶速度	5.3/3.2km/h
Travel brakes行驶制动器	Pressure Release Mechanical Braking
Grade ability爬坡能力	70%(35°)
Ground clearance离地间隙	686mm
Working Ranges工作范围	
Arm length斗杆长度	3000mm
Max. digging reach at ground level地面最大挖掘范围	11814mm
Max. digging depth最大挖掘深度	7800mm
Max. digging heigh最大挖掘高度	10924mm
Max. dumping height最大卸载高度	7615mm
Max. vertical wall digging depth最大垂直挖掘深度	7066mm
Overall length总长度	12090mm
Overall height (to top of boom)总高度（至动臂顶部）	3590mm
Overall width总宽度	3490mm
Shoe width履带宽度	600mm
Overall height (to top of cab)总高度（至驾驶室顶部）	3276mm
Ground clearance of rear end配重离地间隙	1312mm
Min.Ground clearance最小离地间隙	686mm

MC600

Dopting 5.7-inch large-screen LCD liquid crystal display, the machine information display is more comprehensive and intuitive, improve the lumen and screen resolution, and provide dynamic images. Important information is displayed in real time, which can monitor the running status of the machine in real time.

The engine ECU and controller adopt CAN-BUS communication, which makes the power control more accurate and the data collection more comprehensive and timely. Greatly improve the efficiency of the whole machine. Advanced production technology to ensure that the product has a high level of protection. Ensure that the system can operate stably and reliably under adverse working conditions.

采用5.7英寸大屏幕LCD液晶显示屏，使机器信息显示更加全面直观，提升流明和屏幕分辨率，并提供动态图像。重要信息实时显示，可实时监控机器运行状态。

发动机ECU与控制器采用CAN-BUS通讯，使动力控制更加精准，数据采集更加全面及时，大大提高整机效率。先进的生产工艺确保产品具有高防护等级，确保系统在恶劣工况下稳定可靠地运行。



技术参数

Machine Detailed Parameters

Operating Weight and Ground Pressure工作重量和接地比压	
Operating weight工作重量	56000Kg
Ground pressure接地比压	85.3KPa
Engine发动机	
Mode型号	Cummins QSM11-C400
Type类型	6 cylinder inline; turbocharging;intercooling
No. of cylinder气缸数	6
Bore and stroke缸径和冲程	6X125X150(mm)
Displacement排量	10.8L
Power output功率输出	298kw/1800rpm
Hydraulic System液压系统	
Hydraulic pump form类型	Inverter flux control
Travel circuit行走回路压力	34.3MPa
Swing circuit回转回路压力	28.4MPa
Swing speed回转速度	10.4r/min
Bucket铲斗	
Bucket capacity铲斗容量	2.5-3.58m³
Bucket width铲斗宽度	1968mm
Travel System行走系统	
Travel motors行走马达	Variable axial piston motor
Pilot system pressure先导系统压力	4.9Mpa
Travel speed行驶速度	6.1/3.55km/h
Gradeability爬坡能力	70%(35°)
Ground clearance离地间隙	1382mm
Working Ranges工作范围	
Arm length臂长	3000mm
Max. digging reach at ground level地面最大挖掘范围	11176mm
Max. digging depth最大挖掘深度	7114mm
Max. digging heigh最大挖掘高度	10252mm
Max. dumping height最大卸载高度	7150mm
Max. vertical wall digging depth最大垂直墙体挖掘深度	4522mm
Overall length总长度	10252mm
Overall height (to top of boom)总高度（至动臂顶部）	4308mm
Overall width总宽度	3718mm
Shoe width履带宽度	228mm
Overall height (to top of cab)总高度（至驾驶室顶部）	3379mm

MC600J

- 1、Equipped with a domestic famous brand engine and advanced turbocharging technology, ensuring strong power, high-altitude adaptability, lower fuel consumption, and reduced emissions. New cooling fans and large mufflers minimize machine noise.
- 2、High-end hydraulic configuration includes double pump confluence, full hydraulic pilot, 360-degree rotation, and imported components. Features oil cylinder buffer functions, double pump confluence technology for enhanced operation speed, and improved vibration absorption for precise control.
- 3、Improved design elements such as the caterpillar frame, forged bucket rod hinge, whole-arm welding, and wear-resistant steel plates enhance overall durability and service life.
- 4、Expanded visibility with larger windows and skylight glass, ergonomic controls, luxury cab with LCD panel and seat, and air conditioning for comfort and efficiency.
- 5、Electric throttle control, automatic idling function, multi-function LCD monitor, and GPS satellite positioning system for remote diagnostics, maintenance reminders, and efficient operation.
- 6、Ground-level filters and oil-water separator for easy access, large capacity fuel tank, super large toolbox, and longer maintenance cycles due to high-quality components.

- 1、搭载国产知名品牌发动机及先进涡轮增压技术，动力强劲，高海拔适应性强，油耗更低，排放更低。新型冷却风扇和大型消声器使整机噪音降至最低。
- 2、高端液压配置，包括双泵合流、全液压先导、360度旋转等，并采用进口零部件。油缸缓冲功能、双泵合流技术提升作业速度，并增强减震性能，实现精准操控。
- 3、改进的履带架、锻造斗杆铰链、全臂焊接、耐磨钢板等设计元素，提升了整机的耐用性和使用寿命。
- 4、更大的车窗和天窗玻璃、符合人体工程学的控制装置、带液晶仪表盘和座椅的豪华驾驶室以及舒适高效的空调系统，视野更加开阔。
- 5、电子油门控制、自动怠速功能、多功能液晶显示器以及GPS卫星定位系统，可实现远程诊断、维护提醒和高效运行。
- 6、地面级滤清器、油水分离器，检修方便，大容量油箱，超大工具箱，采用优质零部件，维护周期更长。



技术参数

Machine Detailed Parameters

Specifications性能参数	
Bucket Capacity挖斗容量(m³)	3
Swing Speed回转速度(rmp)	0-11
Gradeability最大爬坡角度(°)	35
Max.Bucket Digging Force挖斗最大挖掘力(KN)	325
Max.Arm Digging Force斗杆最大挖掘力(KN)	253
Engine Model发动机型号	OSM11
Power/revolution speed功率/转速(KW/rmp)	298/2000
Tire Model轮胎型号	—
System Pressure系统压力(MPa)	35
Machine size整机尺寸	
Dimension Length*Width*Height外形尺寸长x宽x高(mm)	11690x3360x3810
Cabin Height驾驶室高(mm)	3309
Axle Base轴距(mm)	4621
Wheel(track) Distance轮(轨)距(mm)	2760
Minimum ground clearance最小离地间隙(mm)	602
Tail Swing Radius尾部回转半径(mm)	3760
Working range作业范围	
Max.Digging Height最大挖掘高度(mm)	11142
Max.Dumping Height最大卸载高度(mm)	7779
Max.Digging Depth最大挖掘深度(mm)	5756
Max.Vertical Digging Depth最大垂直挖深(mm)	5064
Max.Digging Radius最大挖掘半径(mm)	10726
Min.Swing Radius最小回转半径(mm)	4390

MC75L

Precise matching design coupled with advanced energy-saving control makes the machine consume less fuel.
The adoption of new cooling fans and large mufflers makes the machine less noisy.
Adopt advanced turbocharging technology to enhance the machine's plateau adaptability.
The unique funnel-shaped fan cover greatly increases the air intake volume of the engine and the system's heat dissipation capacity, ensuring continuous and efficient operation of the machine.

精准的匹配设计，搭配先进的节能控制，使整机油耗更低。
采用新型冷却风扇和大型消声器，降低整机噪音。
采用先进的涡轮增压技术，增强整机高原适应性。
独特的漏斗形风扇罩，大大增加了发动机进气量和系统散热能力，
确保整机持续高效运行。



技术参数

Machine Detailed Parameters

Specifications性能参数	
Bucket Capacity挖斗容量(m³)	0.21
Swing Speed回转速度(rmp)	0-12
Gradeability最大爬坡角度(°)	25
Max.Bucket Digging Force挖斗最大挖掘力(KN)	45
Max.Arm Dgging Force斗杆最大挖掘力(KN)	36
Engine Model发动机型号	YC4DK85
Power/revolution speed功率/转速(KW/rmp)	62.5/2200
Tire Model轮胎型号	8.25-16
System Pressure系统压力(MPa)	24
Machine size整机尺寸	
Dimension Length*Width*Height外形尺寸长x宽x高(mm)	6300X2205X2850
Cabin Height驾驶室高(mm)	2850
Axle Base轴距(mm)	2400
Wheel(track) Distance轮(轨)距(mm)	1675
Minimum ground clearance最小离地间隙(mm)	260
Tail Swing Radius尾部回转半径(mm)	1940
Working range作业范围	
Max.Digging Height最大挖掘高度(mm)	6245
Max.Dumping Height最大卸载高度(mm)	4630
Max.Digging Depth最大挖掘深度(mm)	3820
Max.Vertical Digging Depth最大垂直挖深(mm)	2700
Max.Digging Radius最大挖掘半径(mm)	6360
Min.Swing Radius最小回转半径(mm)	2450
Max.Dozer Blade Lifting Distance推土铲最大离地间隙(mm)	310
Max,Dozer Blade Cutting Distance推土板沉下最大深度(mm)	130

MC75W

Powered by a renowned engine with a variety of power options, it's energy-efficient and environmentally friendly. A new plunger pump hydraulic system delivers smooth compound movements and high speeds. Equipped with wheel-mounted disc brake axles, the vehicle boasts strong load-bearing capacity and excellent adaptability to harsh environments. Standard features include air conditioning, a suspension seat, a large display with a rearview camera, and a well-organized button layout for simple and convenient operation. Its robust and reliable structure is constructed from high-strength manganese plate with reinforced panels in key areas for durability.

搭载知名品牌发动机动力，多种功率可选择，节能环保。
采用新型柱塞泵液压系统，复合动作动作柔和工作速度快搭载轮边减速碟刹车桥，整车承载能力强制动好，更好的适应恶劣环境工作。标配冷暖空调、悬浮座椅、大屏显示器+倒车影像，按键布局合理，操作简单便捷。
结构坚固可靠高强度锰板机身，关键部位附强板，持久耐用。



技术参数

Machine Detailed Parameters

OVERALL DIMENSIONS外形尺寸		
Total length总长		5860 mm
Overall width总宽		2060 mm
Total height总高		2940 mm
Wheelbase轮距		1 550 mm
Wheelbase轴距		2500 mm
boom动臂		3400 mm
Stick斗杆		1850 mm
Scope of work作业范围		
Maximum digging height最大挖掘高度		6987 mm
Maximum unloading height最大卸载高度		5102 mm
Maximum digging depth最大挖掘深度		3362 mm
Maximum vertical digging depth最大垂直挖深		2897 mm
Maximum digging radius最大挖掘半径		6519 mm
Maximum surface excavation radius最大地表挖掘半径		6336 mm
Minimum turning radius of front end前端最小回转半径		2264 mm
Minimum turning radius at rear end后端最小回转半径		1685 mm
Technical Parameters技术参数		
Machine weight整机重量		6.5 T ±5%
Engine Model发动机型号		Yuchai National IV YCF3050-T450
Type型式		Four-cylinder water-cooled electronic injection 四缸水冷电喷
Rated displacement额定排量		2.982L
Power Output功率输出		36.8 KW / 2200 r/min
Walking speed行走速度		0-30 km/h
Gradeability爬坡能力		20 °
Minimum ground clearance最小离地间隙		290 mm
Main pump type主泵型式		variable displacement axial piston pump 变量轴向柱塞泵
Maximum flow最大流量		176 L/min
Rotation speed回转速度		10 r/min
Dourong斗容		0.25m³
diesel tank柴油箱		170L
Hydraulic oil tank液压油箱		110L

MC80L

Equipped with a domestically renowned engine delivering robust power for high-efficiency operations.
Advanced turbocharging technology enhances high-altitude adaptability.
Energy-saving control system reduces fuel consumption through precise hydraulic matching.
Dual-pump flow merging technology increases oil supply to arms/buckets, boosting operational speed.
Forged hinge joints on the dipper arm improve stress distribution and durability.
Spacious cabin with panoramic windows reduces blind spots for safer operation.

搭载国内知名发动机，动力强劲，高效作业。
先进的涡轮增压技术，提升高海拔适应性。
节能控制系统通过精准的液压匹配，降低油耗。
双泵合流技术，增加斗杆/铲斗供油量，提升作业速度。
斗杆采用锻造铰接头，改善应力分布，提升耐用性。
宽敞的驾驶室配备全景窗，减少盲区，确保操作安全。



技术参数
Machine Detailed Parameters

Specifications性能参数	
Bucket Capacity挖斗容量(m³)	0.21
Swing Speed回转速度(rmp)	0-12
Gradeability最大爬坡角度(°)	25
Max.Bucket Digging Force挖斗最大挖掘力(KN)	45
Max.Arm Digging Force斗杆最大挖掘力(KN)	36
Engine Model发动机型号	YC4DK85
Power/revolution speed功率/转速(KW/rmp)	62.5/2200
Tire Model轮胎型号	8.25-16
System Pressure系统压力(MPa)	24
Machine size整机尺寸	
Dimension Length*Width*Height外形尺寸长x宽x高(mm)	6390*2175*2880
Cabin Height驾驶室高(mm)	2880
Axle Base轴距(mm)	2400
Wheel(track) Distance轮(轨)距(mm)	1675
Minimum ground clearance最小离地间隙(mm)	260
Tail Swing Radius尾部回转半径(mm)	2080
Working range作业范围	
Max.Digging Height最大挖掘高度(mm)	6380
Max.Dumping Height最大卸载高度(mm)	4700
Max.Digging Depth最大挖掘深度(mm)	3900
Max.Vertical Digging Depth最大垂直挖深(mm)	2700
Max.Digging Radius最大挖掘半径(mm)	6300
Min.Swing Radius最小回转半径(mm)	2400
Max.Dozer Blade Lifting Distance推土铲最大离地间隙(mm)	370
Max.Dozer Blade Cutting Distance推土板沉下最大深度(mm)	110

MC80W

The MC80W wheeled excavator is a versatile machine that combines power, efficiency, and energy conservation. Its powerful 48kW Yuchai engine provides continuous and stable energy output, enabling it to easily handle complex working conditions. It also excels in fuel efficiency, significantly reducing fuel consumption and lowering operating costs.

Main configuration:

- 1. Yuchai 48kW engine
- 2. Weifu main pump, Husk main valve
- 3. Liansheng 8-ton heavy-duty axle, hydraulic travel, with bulldozer, crushing pipeline, and air conditioning.

MC80W轮式挖掘机是一款集动力、效率和节能于一体的多功能机器。其强劲的48kW玉柴发动机提供持续稳定的动力输出，使其能够轻松应对复杂的工况。此外，它还拥有卓越的燃油效率，显著降低油耗，降低运营成本。

主要配置：

- 1. 玉柴48kW发动机
- 2. 威孚主泵，赫斯克主阀
- 3. 联盛8吨重载桥，液压行走，配备推土铲、破碎管路和空调。



技术参数

Machine Detailed Parameters

OVERALL DIMENSIONS外形尺寸	
Total length总长	6000mm
Total height总高	2840mm
Overall width总宽	2040mm
Cab end驾驶室端部	2840mm
Wheelbase轮距	1700mm
Wheelbase轴距	2380mm
boom动臂	3400mm
Stick斗杆	1850mm
Scope of work作业范围	
Maximum digging height最大挖掘高度	6980mm
Maximum unloading height最大卸载高度	5100mm
Maximum digging depth最大挖掘深度	3360mm
Maximum vertical digging depth最大垂直挖深	2890mm
Maximum digging radius最大挖掘半径	6510mm
Maximum surface excavation radius最大地表挖掘半径	6330mm
Minimum turning radius of front end前端最小回转半径	2265mm
Minimum turning radius at rear end后端最小回转半径	1880mm
Technical Parameters 技术参数	
Machine weight整机重量	6.8 T ±5%
Engine Model发动机型号	YC4FA75Z-T21
Type型式	Four-cylinder water-cooled
Rated displacement额定排量	2.982L
Power Output功率输出	55KW / 2200r /min
Walking speed行走速度	0-30 km/h
Gradeability爬坡能力	2 0 °
Minimum ground clearance最小离地间隙	250 mm
Main pump type主泵型式	variable displacement axial piston pump
Maximum flow最大流量	158 L/min
Rotation speed回转速度	10 r/min
Dourong斗容	0.25m³

MC120L

The MC120L features advanced precision matching design and energy-saving control systems that ensure minimal fuel consumption, greatly reducing operating costs. Equipped with a new cooling fan and large silencers, it effectively lowers noise pollution to provide a more comfortable working environment. Powered by the YCF36100 engine with a rated power of 74 kW at 2200 rpm, combined with advanced turbocharging technology, this excavator maintains stable and efficient operation even in high-altitude and harsh environments. Its unique funnel-shaped fan cover significantly increases air intake and cooling efficiency, ensuring sustained power and reliable heat dissipation during long working hours.

MC120L 采用先进的精密匹配设计和节能控制系统，确保最低油耗，大幅降低运营成本。

配备全新冷却风扇和大型消音器，有效降低噪音污染，提供更舒适的工作环境。

该挖掘机搭载 YCF36100 发动机，额定功率 74 千瓦/2200 转/分，结合先进的涡轮增压技术，即使在高海拔和恶劣环境下也能保持稳定高效的运行。

其独特的漏斗形风扇罩显著提升了进气和冷却效率，确保长时间工作时动力持久，散热可靠。



技术参数

Machine Detailed Parameters

Specifications性能参数	
Bucket Capacity 挖斗容量(m³)	0.4
Swing Speed 回转速度(rmp)	11
Gradeability 最大爬坡角度(°)	25
Max.Bucket Digging Force 挖斗最大挖掘力(KN)	75
Max.Arm Digging Force 斗杆最大挖掘力(KN)	52
Engine Model发动机型号	YC4DK100
Power/revolution speed 功率/转速(KW/rmp)	74/2200
Tire Model 轮胎型号	9.00-20
System Pressure 系统压力(MPa)	35
Machine size整机尺寸	
Dimension Length*Width*Height 外形尺寸长x宽x高(mm)	7285*2270*3010
Cabin Height 驾驶室高(mm)	3010
Axle Base 轴距(mm)	2500
Wheel(track) Distance 轮(轨)距(mm)	1250
Minimum ground clearance 最小离地间隙(mm)	335
Tail Swing Radius 尾部回转半径(mm)	2160
Working range 作业范围	
Max.Digging Height 最大挖掘高度(mm)	8300
Max.Dumping Height 最大卸载高度(mm)	6380
Max.Digging Depth 最大挖掘深度(mm)	4330
Max.Vertical Digging Depth最大垂直挖深(mm)	3950
Max.Digging Radius 最大挖掘半径(mm)	7580
Min.Swing Radius 最小回转半径(mm)	2160
Max.Dozer Blade Lifting Distance 推土铲最大离地间隙(mm)	385
Max.Dozer Blade Cutting Distance 推土板沉下最大深度(mm)	70

MC135W

The MC135W, a new, flexible, efficient, and versatile municipal wheel excavator, debuts with balanced performance. Its flexible mobility, powerful power, smooth operation, powerful crushing, and wide range of applications make it an ideal choice for various urban construction projects.

This wheeled excavator is equipped with the WP4.1G100E311 four-cylinder, water-cooled, electronically fueled, and supercharged engine with a rated displacement of 4.1L. This typical low-speed engine is primarily focused on fuel economy.

The imported Rexroth travel system fully emphasizes the travel quality of the hydraulic travel equipment.

机动灵活高效市政全能型号轮胎式挖掘机MC135W全新登场，各项性能均衡。
移动灵活，动力强劲，作业平稳，破碎有力，并且使用面范极广，MC135W轮胎式挖掘机是城市建设各项工程的理想选择。
该款轮式挖掘机采用WP4.1G100E311发动机型号四缸水冷电喷增压，额定排量4.1L，典型的低转速发动机主要应对燃油经济性。
进口力士乐行走系统充分重视液压行走设备的行走质量。



技术参数

Machine Detailed Parameters

Overall dimensions 外形尺寸	
Total length总长	7300mm
Total height总高	2960mm
Overall width总宽	2300mm
Cab end驾驶室端部	2960mm
Wheelbase轮距	1780mm
Wheelbase轴距	2600mm
Boom length动臂长度	4100mm
Arm length斗杆长度	2200mm
Scope of work作业范围	
Maximum digging depth最大挖掘深度	4400mm
Maximum unloading height最大卸载高度	5950mm
Maximum unloading depth最大卸载深度	3400mm
Maximum digging height最大挖掘高度	7900mm
Maximum digging radius最大挖掘半径	7700mm
Maximum surface excavation radius 最大地表挖掘半径	7440mm
Minimum turning radius最小转弯半径	4200mm
Tail turning radius尾部回转半径	2150mm
Arm digging force斗杆挖掘力	40KN
Bucket digging force铲斗挖掘力	60KN
Technical Parameters技术参数	
Machine weight整机重量	11t
Bucket Capacity铲斗容量	0.5m³
Engine Model发动机型号	WP4.1G100E311
Type型式	Four-cylinder water-cooled electronic injection四缸水冷电喷
Rated displacement额定排量	4.1L
Power Output功率输出	74.2kw
Walking speed行走速度	30km/h
Gradeability爬坡能力	20°
Tire model轮胎型号	9.00-20
Tire quantity轮胎数量	8
Minimum ground clearance最小离地间隙	320mm
Main pump type主泵型式	Electronically controlled plunger pump 电控柱塞泵
Maximum flow最大流量	246 L/min
Rotation speed回转速度	10.5 r/min
Fuel tank capacity燃油箱容量	210L
Hydraulic oil tank capacity液压油箱容量	160L

MC150L

The MC150L Wheel Excavator redefines industry standards with its 110kW powerhouse engine and 91KN bucket digging force, delivering unparalleled performance for mining, large-scale construction, and infrastructure megaprojects.

MC150L 轮式挖掘机凭借其 110kW 动力发动机和 91KN 铲斗挖掘力重新定义了行业标准，为采矿、大型建筑和基础设施大型项目提供了无与伦比的性能。



技术参数

Machine Detailed Parameters

Specifications 性能参数	
Bucket Capacity 挖斗容量(m³)	0.6
Swing Speed 回转速度(rmp)	0-12
Gradeability 最大爬坡角度(°)	25
Max.Bucket Digging Force 挖斗最大挖掘力(KN)	91
Max.Arm Digging Force 斗杆最大挖掘力(KN)	55
Engine Model发动机型号	6BTAA5.9-C178
Power/revolution speed 功率/转速(KW/rmp)	133/2000
Tire Model 轮胎型号	9.00-20
System Pressure 系统压力(MPa)	32
Machine size 整机尺寸	
Dimension Length*Width*Height 外形尺寸长x宽x高(mm)	6770x2550x3370
Cabin Height 驾驶室高(mm)	3100
Axle Base 轴距(mm)	2600
Wheel(track) Distance 轮(轨)距(mm)	1944
Minimum ground clearance 最小离地间隙(mm)	350
Tail Swing Radius 尾部回转半径(mm)	2420
Working range 作业范围	
Max.Digging Height 最大挖掘高度(mm)	8930
Max.Dumping Height 最大卸载高度(mm)	6300
Max.Digging Depth 最大挖掘深度(mm)	5180
Max.Vertical Digging Depth 最大垂直挖深(mm)	4745
Max.Digging Radius 最大挖掘半径(mm)	8200
Min.Swing Radius 最小回转半径(mm)	2650
Max.Dozer Blade Lifting Distance 推土铲最大离地间隙(mm)	400
Max.Dozer Blade Cutting Distance 推土板沉下最大深度(mm)	100

MC150W

The MC150W high-efficiency wheeled excavator is a newly launched fully hydraulic tire excavator from the manufacturer MATCH. It utilizes a renowned engine to ensure a powerful and robust vehicle. Its imported hydraulic system and axle box are precisely matched, ensuring flexible switching between digging and travel modes. With its maneuverability and flexibility, the MC150W wheeled excavator is highly effective in urban operations, offering a wide operating range, long-term stability, and a high return on investment.

MC150W高效轮式挖掘机是迈驰轮式挖掘机厂家全新下线的一款全液压轮胎式挖掘机。采用知名品牌发动机,保证整车强劲有力,进口液压系统与桥箱精准匹配,保证挖掘、行走模式的灵活切换。凭借机动灵活的特点,MC150W轮式挖掘机可以在城镇工作中大显身手,其工作范围大,持久工作稳定,投资回报率高。



技术参数

Machine Detailed Parameters

Model型号	MC150W
Maximum digging height最大挖高mm	8032
Maximum unloading height最大卸高mm	5672
Maximum digging depth最大挖深mm	4623
Maximum vertical digging depth最大垂直挖深mm	3894
Maximum digging radius最大挖掘半径mm	7539
Maximum surface excavation radius最大地表挖掘半径mm	7317
Minimum turning radius of front end前端最小回转半径mm	2588
Minimum turning radius at rear end后端最小回转半径mm	2200
Overall dimensions (L x W x H)外形尺寸（长x宽x高）mm	7250x2495x3125
Cab height司机室高度mm	3220
Wheelbase轮距mm	1902
Wheelbase轴距mm	2770
Dourong斗容m³	0.6
Rotation speed回转速度r/min	14
Low gear travel speed km/h低档行走速度km/h	10
High speed travel km/h高档行走速度km/h	30
Gradeability爬坡能力	30°
Maximum digging force of bucket arm KN最大斗杆挖掘力KN	68.6
Maximum bucket digging force KN最大铲斗挖掘力KN	94.1
Work Quality整机质量kg	14000
System flow L/min系统流量L/min	2-176
Rated power/speed额定功率/转速	Cummins 119Kw/2200rpm
Minimum ground clearance最小离地间隙mm	362 (Bridge 320)
Counterweight ground clearance配重离地间隙mm	1240
boom动臂mm	4300
Stick斗杆mm	2100

MC215L

MC215L wheel hydraulic excavator with super configuration excellent performance imported configuration domestic price.
Domestic famous brand engine, strong power, meet the requirements of efficient operation.
Precise matching design and advanced energy saving control make the machine less fuel consumption.
The use of new cooling fans and large silencers makes the machine less noisy;
Adopt advanced turbocharging technology to enhance the plateau adaptability of the machine;
Unique funnel mouth fan cover, greatly improve the engine air intake and system heat dissipation capacity, to ensure continuous and efficient operation of the machine.

MC215L轮式液压挖掘机，超强配置，卓越性能，进口配置，国产价格。
国产名牌发动机，动力强劲，满足高效作业需求。
精准的匹配设计和先进的节能控制，使机器油耗更低。
采用新型冷却风扇和大型消音器，降低机器噪音；
采用先进的涡轮增压技术，增强机器的高原适应性；
独特的漏斗口风扇罩，大大提高了发动机进气量和系统散热能力，确保机器持续高效运行。



技术参数

Machine Detailed Parameters

Specifications性能参数	
Bucket Capacity挖斗容量(m³)	1.1
Swing Speed回转速度(rmp)	0-12
Gradeability最大爬坡角度(°)	25
Max.Bucket Digging Force挖斗最大挖掘力(KN)	140
Max.Arm Digging Force斗杆最大挖掘力(KN)	100
Engine Model发动机型号	6BTAA5.9
Power/revolution speed功率/转速(KW/rmp)	153/2000
Tire Model轮胎型号	10.00-20
System Pressure系统压力(MPa)	34
Machine size整机尺寸	
Dimension Length*Width*Height外形尺寸长x宽x高(mm)	10006x2500x3515
Cabin Height驾驶室高(mm)	3216
Axle Base轴距(mm)	2850
Wheel(track) Distance轮(轨)距(mm)	1920
Minimum ground clearance最小离地间隙(mm)	380
Tail Swing Radius尾部回转半径(mm)	2412
Working range作业范围	
Max.Digging Height最大挖掘高度(mm)	10329
Max.Dumping Height最大卸载高度(mm)	7397
Max.Digging Depth最大挖掘深度(mm)	6052
Max.Vertical Digging Depth最大垂直挖深(mm)	5682
Max.Digging Radius最大挖掘半径(mm)	10283
Min.Swing Radius最小回转半径(mm)	3458
Max.Dozer Blade Lifting Distance推土铲最大离地间隙(mm)	410
Max.Dozer Blade Cutting Distance推土板沉下最大深度(mm)	125

MC225W

Equipped with Cummins engine which has strong power, Equipped Kawasaki hydraulic components,the operation is accurate.
Adopted side deceleration bridge heavy wheels (special for construction machinery) .
The loading unloading capacity is stronger,and suitable for multiple work environments.
Equipped cold and warm air conditioning, Steering wheel that can be adjusted, Levitation seats, Large color screen, The design of the buttons is reasonable, Luxury cabin.
Design of front-shovel and rear-leg, The structural parts are strengthened, Adapt to all types of complex work.

搭载康明斯发动机，动力强劲，配备川崎液压元件，操作精准。
采用侧减速桥重型轮胎（工程机械专用）。
装卸能力更强，适合多种作业环境。
配备冷暖空调，可调节方向盘，悬浮座椅，彩色大屏幕，按键设计合理，豪华驾驶室。
前铲后腿设计，结构件强化，适应各类复杂作业。



技术参数
Machine Detailed Parameters

Maximum digging height最大挖高(mm)	9670
Maximum unloading height最大卸高(mm)	6817
Maximum digging depth最大挖深(mm)	6559
Maximum digging radius最大挖掘半径(mm)	9897
Maximum surface excavation radius 最大地表挖掘半径(mm)	9697
Minimum turning radius of front end 前端最小回转半径(mm)	3636
Minimum turning radius at rear end 后端最小回转半径(mm)	2855
Overall dimensions (length × width × height) 外形尺寸（长×宽×高）(mm)	9524×2710×3111 (3365cm to the top of the boom) (至动臂顶部3365)
Wheelbase轮距(mm)	1900
Wheelbase轴距(mm)	2850
Bucket capacity斗容(m³)	1.1
Rotation speed回转速度(r/min)	11.5
Low gear travel speed低档行走速度(km/h)	8
High speed travel高档行走速度(km/h)	30
Gradeability爬坡能力	30°
Maximum digging force of bucket arm 最大斗杆挖掘力(KN)	104KN
Maximum bucket digging force 最大铲斗挖掘力(KN)	148KN
Machine weight整机质量(kg)	22300kg
System flow系统流量(L/min)	2×224
Rated pressure额定压力(MPa)	33
Rated power/speed额定功率/转速	Cummins National II engine（康明斯国二发动机）
Minimum ground clearance最小离地间隙(mm)	260
Counterweight ground clearance配重离地间隙(mm)	1250
Boom动臂(mm)	5700
Arm斗杆(mm)	2900

MC10

- 1. High quality hydraulic parts ensure the stable quality.
- 2. Special design on separating engine and radiation space, using enhanced cooling fan to increase cooling efficiency.
- 3. Famous Yuchi Engine, high efficiency, low repair cost.
- 4. equipped with double fuel filter to guarantee fuel purity to protect engine.
- 5. extend hydraulic line for various attachments.
- 6. Full sealed cabin with A/C and comfort seat make operator easy to work.
- 7. Opening covering parts makes the maintenance easy to proceed.

- 1. 高品质液压部件，确保质量稳定。
- 2. 特殊设计，发动机与散热空间分离，采用加强型冷却风扇，提高冷却效率。
- 3. 选用名牌宇驰发动机，效率高，维修成本低。
- 4. 配备双燃油滤清器，确保燃油纯度，保护发动机。
- 5. 可延伸液压管路，适用于各种属具。
- 6. 全密封驾驶室，配备空调和舒适型座椅，操作更轻松。
- 7. 可打开的覆盖件，维护更便捷。



技术参数

Machine Detailed Parameters

Specifications性能参数	
Bucket Capacity挖斗容量(m³)	0.023
Swing Speed回转速度(rmp)	0-13
Gradeablity最大爬坡角度(°)	30
Max.Bucket Digging Force挖斗最大挖掘力(KN)	7.2
Max.Arm Digging Force斗杆最大挖掘力(KN)	4.6
Engine Model发动机型号	KD192F—1
Power/revolution speed功率/转速(KW/rmp)	7/3000
Tire ode轮胎型号	—
System Pressure系统压力(MPa)	16
Machine size整机尺寸	
Dimension Length*Width*Height外形尺寸长x宽x高(mm)	2840x880x2220
Cabin Height驾驶室高(mm)	2220
Axle Base轴距(mm)	900
Wheel(track) Distance轮(轨)距(mm)	660
Minimum ground clearance最小离地间隙(mm)	132
Tail Swing Radius尾部回转半径(mm)	800
Working range作业范围	
Max.Digging Height最大挖掘高度(mm)	2600
Max.Dumping Height最大卸载高度(mm)	1830
Max.Digging Depth最大挖掘深度(mm)	1715
Max.Vertical Digging Depth最大垂直挖深(mm)	15901
Max.Digging Radius最大挖掘半径(mm)	3065
Min.Swing Radius最小回转半径(mm)	1480

MC15

- 1. Affordable products with long service life, ranging from 0.6 tons to 60 tons to meet your specific needs.
- 2. Customization options available for our products.
- 3. Sufficient profit margins for suppliers.
- 4. After-sales service guaranteed for our products within 1-3 years.
- 5. Product testing to ensure quality before delivery.
- 6. Free publicity for suppliers in their country.
- 7. Customized colors and product trademarks available.

- 1. 价格实惠，使用寿命长，产品重量从0.6吨到60吨不等，可满足您的特定需求。
- 2. 我们提供定制产品。
- 3. 为供应商提供充足的利润空间。
- 4. 我们提供1-3年内的产品售后服务保证。
- 5. 交货前进行产品测试，确保质量。
- 6. 为供应商在其所在国家/地区提供免费宣传。
- 7. 提供定制颜色和产品商标。



技术参数

Machine Detailed Parameters

Specifications性能参数	
Bucket Capacity挖斗容量(m³)	0.025
Swing Speed回转速度(rmp)	11-13
Gradeability最大爬坡角度(°)	30
Max.Bucket Digging Force挖斗最大挖掘力(KN)	9
Max.Arm Digging Force斗杆最大挖掘力(KN)	5.5
Engine Model发动机型号	D722
Power/revolution speed功率/转速(KW/rmp)	10.2/2500
Tire Model轮胎型号	—
System Pressure系统压力(MPa)	20
Working range作业范围	
Max.Digging Height最大挖掘高度(mm)	2955
Max.Dumping Height最大卸载高度(mm)	2077
Max.Digging Depth最大挖掘深度(mm)	2017
Max.Vertical Digging Depth最大垂直挖深(mm)	1610
Max.Digging Radius最大挖掘半径(mm)	3529
Min.Swing Radius最小回转半径(mm)	—
Max.Dozer Blade Lifting Distance推土铲最大离地间隙(mm)	236
Max.Dozer Blade Cutting Distance推土板沉下最大深度(mm)	229
Machine size整机尺寸	
Total Length总长(运输时)(mm)	3329*990/1300*2267
Total Width总宽(运输/作业)(mm)	990/1300
Total Height总高(运输时)(mm)	2290
Cabin Height驾驶室高(mm)	2267
Axle Base轴距(mm)	1190
wheel(track)Distance轮(轨)距(mm)	790
Minimum ground clearance最小离地间隙(mm)	153
Tail Swing Radius尾部回转半径(mm)	655

MC18

This MC18 mini crawler excavator is our figured product equipped with swing boom,its specially fits in gardens and personeal house project use.

这款 MC18 小型履带式挖掘机是我们配备回转臂的定制产品，特别适合花园和个人住宅项目使用。



技术参数

Machine Detailed Parameters

Specifications性能参数	
Bucket Capacity挖斗容量(m³)	0.06
Swing Speed回转速度(rmp)	10-12
Gradeablity最大爬坡角度(°)	35
Max.Bucket Digging Force挖斗最大挖掘力(KN)	14
Max.Arm Digging Force斗杆最大挖掘力(KN)	10
Engine Model发动机型号	3L15p25
Power/revolution speed功率/转速(KW/rmp)	18.4/2350
Tire Model轮胎型号	—
System Pressure系统压力(MPa)	18
Machine size整机尺寸	
Dimension Length*Width*Height外形尺寸长x宽x高(mm)	3865x1050x2270
Cabin Height驾驶室高(mm)	2270
Sproket to Idler轴距(mm)	1230
Wheell (Track) Guage轮(轨)距(mm)	820
Minimum ground clearance最小离地间隙(mm)	210
Tail Swing Radius尾部回转半径(mm)	1125
Working range作业范围	
Max.Digging Height最大挖掘高度(mm)	3365
Max.Dumping Height最大卸载高度(mm)	2385
Max.Digging Depth最大挖掘深度(mm)	2050
Max.Vertical Digging Depth最大垂直挖深(mm)	1725
Max.Digging Radius最大挖掘半径(mm)	3860
Min.Swing Radius最小回转半径(mm)	1720
Max.Dozer Blade Lifting Distance推土铲最大离地间隙(mm)	230
Max.Dozer Blade Cutting Distance推土板沉下最大深度(mm)	275
Boom Swing Angle (Left)动臂摆动角度(左)°	75
Boom Swing Angle (Right)动臂摆动角度(右)°	45

MC20

MATCH MC20 Crawler Excavator for Construction, Mining & Port Works is designed for small works, small projects, in garden, farmland, vegetable greenhouse, orchards, landscaping, trenching, pipeline laying, material handling, earthwork, rural construction, municipal construction, afforestation, road maintenance, crushing, demolition and other fields. It is with small engine, simple design, easy to maintain, comfortable and safe operation, energy saving, environmental protection and high efficiency.

MATCH MC20履带式挖掘机适用于建筑、采矿和港口工程，专为小型工程、小型项目而设计，适用于花园、农田、蔬菜温室、果园、园林绿化、挖沟、管道铺设、物料搬运、土方工程、农村建设、市政建设、绿化、道路维护、破碎、拆除等领域。该挖掘机发动机小，设计简洁，维护方便，操作舒适安全，节能、环保、高效。



技术参数

Machine Detailed Parameters

Specifications性能参数	
Bucket Capacity挖斗容量(m³)	0.07
Swing Speed回转速度(rmp)	0-9
Gradeability最大爬坡角度(°)	35
Max.Bucket Digging Force挖斗最大挖掘力(KN)	18
Max.Arm Digging Force斗杆最大挖掘力(KN)	11
Engine Model发动机型号	KUBOTA D1105
Power/revolution speed功率/转速(KW/rmp)	14.2/2000
Tire Model轮胎型号	
System Pressure系统压力(MPa)	21.5
Working range作业范围	
Max.Digging Height最大挖掘高度(mm)	3700
Max.Dumping Height最大卸载高度(mm)	2440
Max.Digging Depth最大挖掘深度(mm)	2400
Max.Vertical Digging Depth最大垂直挖深(mm)	2025
Max.Digging Radius最大挖掘半径(mm)	4040
Min.Swing Radius最小回转半径(mm)	1610
Max.Dozer Blade Lifting Distance推土铲最大离地间隙(mm)	240
Max.Dozer Blade Cutting Distance推土板沉下最大深度(mm)	270
Machine size整机尺寸	
Total Length总长(运输时)(mm)	3555
Total Width总宽(运输/作业)(mm)	990/1300
Total Height总高(运输时)(mm)	2290
Cabin Height驾驶室高(mm)	2290
Axle Base轴距(mm)	1230
Wheel(track) Distance轮(轨)距(mm)	760
Minimum ground clearance最小离地间隙(mm)	150
Tail Swing Radius尾部回转半径(mm)	650

MC22

For Heavy-Duty Work:
0.1 m³ bucket handles 4x more material than MC10 per scoop.
22.1 kW engine powers through tough jobs (concrete breaking, deep trenches).
2450 mm digging depth vs. MC10's 1838 mm – ideal for utility work.
Stability on Rough Terrain:
210 mm ground clearance (vs. 125 mm on MC10) for rocky/muddy sites.
1050 mm track width provides better balance on slopes.
Versatile Attachments:
70°/50° boom swing vs. fixed boom on MC22 – reaches around obstacles.
310 mm dozer blade cut (vs. 237 mm) for efficient backfilling.
Best For: Large-scale landscaping, construction sites, mining support.

重载作业:
0.1 立方米铲斗每铲可处理比 MC10 多 4 倍的物料。
22.1 千瓦发动机动力强劲，可轻松应对各种艰巨作业（例如混凝土破碎、深沟开挖）。
2450 毫米挖掘深度（MC10 为 1838 毫米）——非常适合公用事业作业。
崎岖地形下的稳定性:
210 毫米离地间隙（MC10 为 125 毫米），适用于岩石/泥泞场地。
1050 毫米履带宽度，在斜坡上提供最佳的平衡性。
多功能附件:
MC22 的动臂摆动角度为 70°/50°，而非固定动臂，可轻松绕过障碍物。
310 毫米推土铲铲齿（MC10 为 237 毫米），可高效回填。
最适合：大型园林绿化、建筑工地、采矿支护。



技术参数

Machine Detailed Parameters

Specifications性能参数	
Bucket Capacity挖斗容量(m³)	0.1
Swing Speed回转速度(rmp)	0-12
Gradeability最大爬坡角度(°)	30
Max.Bucket Digging Force挖斗最大挖掘力(KN)	15.3
Max.Arm Digging Force斗杆最大挖掘力(KN)	10.5
Engine Model发动机型号	3TE30
Power/revolution speed功率/转速(KW/rmp)	22.1/2300
System Pressure系统压力(MPa)	18
Machine size整机尺寸	
Dimension Length*Width*Height外形尺寸长x宽x高(mm)	4170x1300x2280
Cabin Height驾驶室高(mm)	2280
Axle Base轴距(mm)	1230
Wheel(track) Distance轮(轨)距(mm)	1050
Minimum ground clearance最小离地间隙(mm)	230
Tail Swing Radius尾部回转半径(mm)	1180
Working range作业范围	
Max.Digging Height最大挖掘高度(mm)	3700
Max.Dumping Height最大卸载高度(mm)	2290
Max.Digging Depth最大挖掘深度(mm)	2450
Max.Vertical Digging Depth最大垂直挖深(mm)	2160
Max.Digging Radius最大挖掘半径(mm)	4370
Min.Swing Radius最小回转半径(mm)	2020
Max.Dozer Blade Lifting Distance推土铲最大离地间隙(mm)	240
Max.Dozer Blade Cutting Distance推土板沉下最大深度(mm)	310
Boom Swing Angle (Left)动臂摆动角度(左)°	70
Boom Swing Angle (Right)动臂摆动角度(右)°	50

MC27

1. Brutal Digging Force for Tough Materials:
23.5 kN Bucket Force (2x stronger than standard mini excavators) – crushes concrete, hardpan, and rocky soil effortlessly.
14 kN Arm Force for smooth, controlled lifting of heavy debris.
2. Extreme Terrain Mastery:
58° Max Climb Angle – Works on steep slopes where others slip.
285 mm Ground Clearance – Glides over rough terrain without belly damage.
Steep slope excavator, all-terrain digger, high-clearance construction equipment.
1. 强劲挖掘力，轻松应对坚硬物料:
23.5 kN 铲斗力（比标准小型挖掘机强两倍）——轻松破碎混凝土、硬土层和岩石。
14 kN 斗杆力，可平稳、可控地提升重型碎屑。
高挖掘力挖掘机，23.5 kN 挖掘力，混凝土破碎机。
2. 极致地形掌控:
58° 最大爬坡角度——即使在其他机器容易打滑的陡坡也能轻松应对。
285 mm 离地间隙——在崎岖地形上也能轻松滑行，不会损坏机腹。
陡坡挖掘机,全地形挖掘机,高离地间隙建筑设备。



技术参数

Machine Detailed Parameters

Specifications性能参数	
Bucket Capacity挖斗容量(m³)	0.1
Swing Speed回转速度(rmp)	1-10
Gradeability最大爬坡角度(°)	58
Max.Bucket Digging Force挖斗最大挖掘力(KN)	23.5
Max.Arm Digging Force斗杆最大挖掘力(KN)	14
Engine Model发动机型号	D1105-E4B
Power/revolution speed功率/转速(KW/rmp)	14/2000
Tire Model轮胎型号	—
System Pressure系统压力(MPa)	20.5
Machine size整机尺寸	
Dimension Length*Width*Height外形尺寸长x宽x高(mm)	4195x1550x2480
Cabin Height驾驶室高(mm)	2480
Axle Base轴距(mm)	1550
Wheel(track) Distance轮(轨)距(mm)	1250
Minimum ground clearance最小离地间隙(mm)	285
Tail Swing Radius尾部回转半径(mm)	860
Working range作业范围	
Max.Digging Height最大挖掘高度(mm)	4427
Max.Dumping Height最大卸载高度(mm)	3005
Max.Digging Depth最大挖掘深度(mm)	2830
Max.Vertical Digging Depth最大垂直挖深(mm)	2500
Max.Digging Radius最大挖掘半径(mm)	4835
Min.Swing Radius最小回转半径(mm)	2160
Max.Dozer Blade Lifting Distance推土铲最大离地间隙(mm)	308
Max.Dozer Blade Cutting Distance推土板沉下最大深度(mm)	360

MC35

MC35 crawler excavator is a china famous brand MATCH, which researched and developed with world latest technical standard.

It is a new kind of product characterized by high efficiency , safety, convenience, beauty.

Rubber track, the excavator adopted the KUBOTA engine with Euro 5 and EPA4 emission ,with dozer blade.

The machine can deflection to left and right to meet the different digging direction .

Hydraulic pilot servo handle controlling system ,easy to operation , campact size meet the small working space.

MC35履带式挖掘机是中国著名品牌MATCH，采用世界最新技术标准研发而成。

它是一种高效、安全、方便、美观的新型产品。

橡胶履带，挖掘机采用久保田发动机，符合欧5和EPA4排放标准，带推土铲。

机器可以左右偏转以满足不同的挖掘方向。

液压先导伺服手柄控制系统，操作方便，体积小巧，适合狭小的工作空间。



技术参数

Machine Detailed Parameters

Specifications性能参数	
Bucket Capacity挖斗容量(m³)	0.12
Swing Speed回转速度(rmp)	1-11
Gradeablity最大爬坡角度(°)	30
Max.Bucket Digging Force挖斗最大挖掘力(KN)	30
Max.Arm Digging Force斗杆最大挖掘力(KN)	18
Engine Model发动机型号	KUBOTAD1703
Power/revolution speed功率/转速(KW/rmp)	18.2/2200
Tire Model轮胎型号	—
System Pressure系统压力(MPa)	22.5
Working range作业范围	
Max.Digging Height最大挖掘高度(mm)	4800
Max.Dumping Height最大卸载高度(mm)	3406
Max.Digging Depth最大挖掘深度(mm)	3208
Max.Vertical Digging Depth最大垂直挖深(mm)	2957
Max.Digging Radius最大挖掘半径(mm)	5480
Min.Swing Radius最小回转半径(mm)	2530
Max.Dozer Blade Lifting Distance推土铲最大离地间隙(mm)	365
Max.Dozer Blade Cutting Distance推土板沉下最大深度(mm)	385
Machine size整机尺寸	
Total Length总长(运输时)(mm)	4915
Total Width总宽(运输/作业)(mm)	1720
Total Height总高(运输时)(mm)	2525
Cabin Height驾驶室高(mm)	2290
Axle Base轴距(mm)	1670
Wheel(track) Distance轮(轨)距(mm)	1420
Minimum ground clearance最小离地间隙(mm)	295
Tail Swing Radius尾部回转半径(mm)	870